

INDIA'S NO-1

Recommended Stage Light Brand

CO5PO



| Quality

| Durability

| Reliability

10M⁺

users world wide

www.co5po.com

10 M⁺ Users World Wide

CO5PO

THE BRAND THAT PEOPLE RECOMMEND NATURALLY.

RANGE OF PARLIGHT SERIES



RGB

ACTUAL
54X3W

Heavy
duty
body

CP001 - H



RGBW

ACTUAL
54X3W

Heavy
duty
body

CP001 - H



RGB

ACTUAL
54X4W

Heavy
duty
body

CP002 - H



RGB

ACTUAL
54X4W

Heavy
body
2M wire

CP012 - H



RGB

ACTUAL
54X3W

Durability

CP007 - H



WARM
WHITE

ACTUAL
54X3W

Durability

CP005 - H



RGB

ACTUAL
54X5W

Heavy
duty
body

CP005 - H



RGB

ACTUAL
60X2W

ABS
Plastic

CP60 - H



WARM
& WHITE

ACTUAL
4X50W

Heavy
body

CP 1/2 - H



WARM

ACTUAL
4X50W

Heavy
body

CP 1/2 - H



RGB

ACTUAL
4X50W

Heavy
body

CP 1/2-H-RGB



RGB

ACTUAL
54X3W

IP 65
water
proof

CP008 - H

10 M⁺ Users World Wide

CO5PO

CO5PO MOVING HEADS ARE KNOWN FOR THEIR ROBUST BUILD QUALITY, HIGH PRECISION, AND LONG-TERM RELIABILITY.

RANGE OF SHARPY



BSW

POWERED BY
OSRAM
GERMANY

CTO
CMY

BSW SHARPY
LB 380 -3D



LASER
PRISM

POWERED BY
OSRAM
GERMANY

LINEAR
DIMMING
0-100%

RANGER 750
MOVING HEAD



LASER
PRISM

POWERED BY
OSRAM
GERMANY

540°, 270°

AVATAR 680
MOVING HEAD



EXTREMELY
HIGH
LUMINANCE

NARROW
BEAM
ANGLE

ELLIPTICAL
PRISM

STORM 580
MOVING HEAD



INNOVATIVE
TECHNOLOGY

POWERED BY
CREE XP-E
Taiwan

150W

LB 150
MINI SHARPY



INNOVATIVE
TECHNOLOGY

POWERED BY
CREE XP-E
Taiwan

120W

CP009
MINI SHARPY



RGBW
4-IN-1

POWERED BY
CREE XP-E
Taiwan

19x40W

CP018 BEES EYE



RGBW
4-IN-1

POWERED BY
CREE XP-E
Taiwan

19x15W

CP018 BEES EYE



RGBW
4-IN-1

POWERED BY
CREE XP-E
Taiwan

7x40W

CP018 STAR
BEES EYE

10 M⁺ Users World Wide

CO5PO

OFFERS CREATIVE FLEXIBILITY AND CONTROL FOR LIGHTING DESIGNERS.

Maxuz



ARENA



TIGER TOUCH PLUS



ST3 TIGER TOUCH



X3 MINI PEARL



TIGER TOUCH II



AI CONSOLE

CO5PO



MINI PEARL 1024



PILOT 2000 DMX,
DMX 240



DMX 512,
DMX JW-40

PROFILE LIGHTS



CP006 PROFILE ZOOM
200W W+WW



CP006 PROFILE ZOOM
200W W+RGB



CP006 PROFILE ZOOM
300W W+WW



CP006 PROFILE ZOOM
300W RGB

10 M+ Users World Wide

CO5PO

CO5PO CONTINUOUSLY LAUNCHES CUTTING-EDGE TECHNOLOGY
WITH REAL-WORLD FUNCTIONALITY

CLIMATE CREATIONS



SMOKER 1500,
2000WATTS



SMOKER
3000-F3000



COLOUR COLUMN
SMOKER 1500 WTS



HAZE MACHINE CLOUD
1000 WATTS, 1500WATTS



COLD SPARK
MACHINE



LOW FOG MACHINE



SNOW MACHINE 1200



BUBBLE MACHINE
WITH SMOKE



CONFETTI
MACHINE BIG



CONFETTI GUNS
BASIC & WITH RGB LED

LASERS



B20 RGB LASER



15 WATT LASER



B10 RGB LASER



B7 RGB LASER



B5 RGB LASER 5W



B10 4 HEAD RGB LASER



4/8 EYE WIPER
BAR LASERS



6EYE RGB LASER

FACE LIGHTS & FOLLOW SPOT



200W COB
FRESNEL LIGHT



300W COB
FRESNEL LIGHT



LM070 200W W+WW



CP006
FOLLOW SPOT 350

10 M⁺ Users World Wide


CO5PO

OFFERS BUDGET TO PREMIUM PRODUCT RANGES TO SUIT EVERY CUSTOMER SEGMENT.

EFFECT LIGHTS



DOUBLE HEAD
DAMRU



4IN1-6 EYE BEAM
MOVING HEAD LIGHT



SPIDER
MOVING HEAD



LUTTU BALL LASER




LED ALPHABET
STROBE



MATRIX STROBE




LINEAR STROBE



LED FAN



RETRO MATRIX BLINDOR



MATRIX LED



PIXEL BAR AND
WALL WASHER



CO5PO FLOOD LENS TYPE
200 W, 100 W & 50 W

LIGHT STAND



3M LIGHT STAND
& 3M HAND CRANK STAND



4M HAND-CRANK
STAND



5.5M HEAVY - DUTY
LIFTING BRACKET STAND



RAIN PROTECTION
COVERS



RAIN PROTECTION COVERS
TRANSPARENT

ACCESSORIES



CLAMPS & OILS



CABLES



POWER SEQUENCE



CONNECTORS



SPLITTER

10 M⁺ Users World Wide



IT'S NOT JUST A LIGHTING BRAND — IT'S THE ORIGIN OF THE MODERN STAGE LIGHT CONCEPT

BLINDOR SERIES



2EYE BLINDOR W+WW



2EYE RGB
HEAVY BODY



2EYE BLINDOR WW



2EYE BLINDOR RGB



2EYE BLINDOR W+WW+RGB
-DOUBLE RING



2EYE BLINDOR WW+RGB
-SINGLE RING



4EYE BLINDOR W+WW



4EYE BLINDOR RGB

PRECISION IN EVERY NOTE POWER IN EVERY BEAT

 **EXPERIENCE THE GERMAN
ENGINEERING IN SOUND**



Model	LD5000	LD9000	LD12000
CH	2CH		
@8 Ω Output Power/CH*	2X1300W	2X1500W	2X2000W
@4 Ω Output Power/CH**	2X1500W	2X2500W	2X3000W
@4 Ω Peak Power/CH**	2X2300W	2X3200W	1X4100W
@8 Ω Bridge Output Power**	1X3500W	1X4000W	1X5000W
Phase Between input channels		±0.1	
Frequency Response(20Hz-20KHz)	±0.5dB		
Total harmonic distortion	<0.1%		
Slew rate	30V/us	30V/us	30V/us
Damping coefficient (100Hz)	>800:1	>1000:1	>1000:1
Signal Noise Ration	102dB(A)		
Channel separation	>65dB		
Impedance(balanced/unbalanced)	20KΩ balanced/ 10KΩ unbalanced		
Sensitivity	0.775V、1V、32dB		
Net Weight/Gross Weight	16kg/18kg	17kg/18.7kg	18kg/19.7kg
Dimensions	483mmX333mmX88mm		
Packing Dimensions	580mmX450mmX170mm		
Power Requirements	AC230V/50-60Hz		

10 M⁺ Users World Wide

TRUSTED BY MILLIONS OF CONSUMERS, PROFESSIONALS, AND ARTISTS FOR DECADES.

INDIA'S NO-1

Recommended Stage Light Brand



- MAINTAINS STRICT QUALITY CONTROL STANDARDS.
- 24*7 CUSTOMER SUPPORT FOR QUICK AFTER-SALES INQUIRIES
- QUICK AND RELIABLE SERVICE CENTRES BUILD CUSTOMER TRUST.
- LONG-STANDING PRESENCE IN THE COUNTRY SINCE 1999

